

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. – 2. (Cancelled)

3. (Previously Presented) A data merge unit for providing an interleaved data stream, the data stream including data frames received on two or more input channels, wherein complete data frames from each of the two or more input channels are arranged in time-slots of the interleaved data stream, the data merge unit comprising:

an input unit to receive data frames from two or more input channels;

a frame merge buffer arranged to receive data frames from the two or more input channels via the input unit and store said data frames; and

an output generator to generate the interleaved data stream, the output generator being configured to select complete data frames from the frame merge buffer and arrange said complete data frames in the interleaved data stream,

in which the output generator is operable in a first mode to select complete data frames in the frame merge buffer from an identified input channel and output the selected frames in a corresponding time-slot of the interleaved data stream for that input channel independently of other input channels and, in a second mode in which complete data frames from two or more of the two or more input channels are selected from the frame merge buffer and merged and provided in a common time-slot of the interleaved data stream.

4. (Original) A data merge unit according to claim 3, in which when operating in the second mode, a look up table of values is provided to identify one or more complete data frames from one or more input channels for transfer from the frame merge buffer for merging with one or more complete data frames from one or more other input channels in a common time-slot of the interleaved data stream.

5. (Original) A data merge unit according to claim 4, in which the look up table of values is generated in dependence on the identified ends of the data frames.

6. (Original) A data merge unit according to claim 5, in which each entry in the look up table comprises an identified input channel, each entry corresponding to the end of a data frame received on the corresponding identified input channel.

7. (Original) A data merge unit according to claim 6, in which as data is received by the frame merge buffer, if it is determined that a component data word of a data frame is the last word of the frame, a corresponding entry is made in the look up table.

8. (Currently Amended) A data merge unit for providing an interleaved data stream, the data stream including data frames received on two or more input channels, wherein complete data frames from each of the two or more input channels are arranged in time-slots of the interleaved data stream, the data merge unit comprising:

an input unit to receive data frames from two or more input channels;

a frame merge buffer arranged to receive data frames from the two or more input channels via the input unit and store said data frames; and

an output generator to generate the interleaved data stream, the output generator being configured to select complete data frames of a networking protocol from the frame merge buffer and arrange said complete data frames of the said networking protocol in the interleaved data stream A data merge unit according to claim 1, in which the input unit comprises a round-robin input arbiter arranged to service each of the two or more input channels and provide data frames therefrom to the frame merge buffer.

9. (Original) A data merge unit according to claim 4, in which the output generator comprises a round-robin output arbiter arranged, when the data merge unit is operating in the second mode, to read and output a complete data frame from a corresponding input channel in the frame merge buffer in dependence on values obtained from the look up table.

10. (Currently Amended) A data merge unit according to claim [[1]] 3, the data merge unit being a hardware data merge unit.

11. (Original) A data merge unit according to claim 10, in which the data merge unit is arranged in hardware selected from the group consisting of one or more Application Specific

Integrated Circuits, one or more Field Programmable Gate Arrays, or any other suitably configured hardware.

12. (Currently Amended) A network analyzer, comprising:
  - a data merge unit according to claim [[1]] 3; and
  - a logic unit to analyze the interleaved data stream provided by said data merge unit.
13. (Previously Presented) A network analyzer according to claim 12, in which the logic unit is configured to provide one or more functions selected from the group consisting of network management and network load balancing.
14. – 15. (Cancelled)
16. (Previously Presented) A method of producing an interleaved data stream of data frames received on two or more input channels in a network analyzer, the interleaved data stream being made up of complete data frames from each of the two or more input channels arranged in defined time-slots, the method comprising:
  - receiving at the network analyzer one or more data frames on two or more input channels;
  - storing said received data frames in a frame merge buffer; and
  - selecting complete data frames from the frame merge buffer and arranging said complete data frames in the interleaved data stream, in which the method comprises:
    - in a first mode outputting complete data frames from a selected input channel in a corresponding time-slot of the interleaved data stream for that input channel independently of other input channels and in a second mode merging complete data frames from at least two of the two or more input channels and providing said merged data in a common time-slot of the interleaved data stream.
17. (Original) A method according to claim 16, in which when operating in the second mode, a look up table of values is provided and used to identify one or more complete data frames from one or more input channels for transfer from the frame merge buffer for merging with one or more complete data frames from one or more other input channels in a common time-slot of the interleaved data stream.

18. (Original) A method according to claim 17, in which values in the look up table are generated in dependence on ends of data frames.
19. (Currently Amended) A method according to claim ~~[[14]]~~ 16, in which the interleaved data stream is generated at full line rate of the input channels.
20. (Currently Amended) A method of analyzing a network ~~using a network analyzer~~, the method comprising:  
using a network analyzer, producing an interleaved data stream of complete data frames received on two or more input channels according to the method of claim ~~[[14]]~~ 16, the data channels associated with a network to be analyzed;  
providing said interleaved data stream to logic to analyze said data stream; and,  
analyzing said data stream, thereby analyzing the network.
21. – 23. (Cancelled)